

# SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

## GENERAL INFORMATION

Body Styles \_\_\_\_\_ Regular Cab, Quad Cab<sup>®</sup> and Crew Cab

Assembly Plants:

Regular Cab \_\_\_\_\_ St. Louis, Missouri

Quad Cab<sup>®</sup> \_\_\_\_\_ Dodge City (Warren, MI)

Crew Cab \_\_\_\_\_ Dodge City (Warren, MI), and St. Louis, Missouri

EPA Vehicle Class \_\_\_\_\_ Standard Pickup

Introduction Date \_\_\_\_\_ January 2008

## ENGINE: 3.7-LITER V-6

Availability \_\_\_\_\_ Standard – 2WD Regular Cab or 2WD Quad Cab<sup>®</sup>

Type and Description \_\_\_\_\_ 90 degree V-6, liquid-cooled with balance shaft

Displacement \_\_\_\_\_ 226 cu in (3701 cu cm)

Bore x Stroke \_\_\_\_\_ 3.66 in x 3.57 in (93.0 mm x 90.8mm)

Valve System \_\_\_\_\_ Chain-driven SOHC, 12 valves, Normally Open check-valve Lash Adjusters

Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless

Construction \_\_\_\_\_ Cast iron block and bedplate, aluminum alloy heads, balance shaft

Compression Ratio \_\_\_\_\_ 9.7:1

Power (SAE net) \_\_\_\_\_ 210 bhp (156 kW) @ 5200 rpm

Torque (SAE net) \_\_\_\_\_ 235 lb-ft (319 N·m) @ 4000 rpm

Max. Engine Speed \_\_\_\_\_ 6000 rpm (electronically-limited)

Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R + M)/2

Oil Capacity \_\_\_\_\_ 5.0 qt (4.7 L)

Coolant Capacity \_\_\_\_\_ 11.3 qt (10.71 L)

Emissions Controls \_\_\_\_\_ 3-way catalytic converter and internal engine features<sup>1</sup>

Estimated EPA Fuel Economy (MPG City/Hwy):

Manual Transmission \_\_\_\_\_ 15/20

Automatic Transmission \_\_\_\_\_ 14/20

<sup>1</sup> Meets Tier 1 requirements in all 50 states.

## ENGINE: 4.7-LITER V-8

Availability	_____	Standard – all 4WD and Crew Cab
Type and Description	_____	90 degree V-8, liquid-cooled
Displacement	_____	287 cu in (4701 cu cm)
Bore x Stroke	_____	3.66 in x 3.40 in (93.0 mm x 86.5 mm)
Valve System	_____	Chain-driven SOHC, 16 valves, Normally Open check-valve Lash Adjusters
Fuel Injection	_____	Sequential, multi-port, electronic, returnless
Construction	_____	Cast iron block and bedplate, aluminum alloy heads
Compression Ratio	_____	9.8:1
Power (SAE net)	_____	310 bhp (231 kW) @ 5650 rpm
Torque (SAE net)	_____	330 lb-ft (447 N·m) @ 3950 rpm
Max. Engine Speed	_____	6000 rpm (electronically-limited)
Fuel Requirement	_____	Unleaded regular, 87 octane (R + M)/2
Oil Capacity	_____	6.0 qt (5.7 L)
Coolant Capacity	_____	10.8 qt (10.23 L)
Emissions Controls:		
Federal	_____	3-way catalytic converter and internal engine features <sup>2</sup>
ULEV	_____	Three 3-way catalytic converters and internal engine features <sup>3</sup>
Estimated EPA Fuel Economy (MPG City/Hwy):		
Two-Wheel Drive	_____	13/19
Four-Wheel Drive	_____	13/18

<sup>2</sup> Meets Federal Tier 1 emission requirements in all states except California and Massachusetts.

<sup>3</sup> Meets California ULEV Ultra-Low Emission Vehicle requirements in California and Massachusetts.

## ENGINE: 5.7-LITER HEMI® V-8

Availability \_\_\_\_\_ Optional  
Type and Description \_\_\_\_\_ 90 degree V-8, liquid-cooled  
Displacement \_\_\_\_\_ 345 cu in (5654 cu cm)  
Bore x Stroke \_\_\_\_\_ 3.92 in x 3.58 in (99.5 mm x 90.9 mm)  
Valve System \_\_\_\_\_ Variable Cam Timing, Pushrod-operated overhead 16 valves,  
hydraulic lifters with roller followers  
Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
Construction \_\_\_\_\_ Deep-skirt cast iron block with cross-bolted main bearing caps,  
aluminum alloy heads with hemispherical combustion chambers  
Compression Ratio \_\_\_\_\_ 10.5:1  
Power (SAE net) \_\_\_\_\_ 380 bhp (283 kW) @ 5600 rpm  
Torque (SAE net) \_\_\_\_\_ 404 lb-ft (548 N·m) @ 4000 rpm  
Max. Engine Speed \_\_\_\_\_ 5800 rpm  
Fuel Requirement \_\_\_\_\_ Unleaded mid-grade, 89 octane (R+M)/2 – recommended,  
Unleaded regular, 87 octane (R+M)/2 – acceptable  
Oil Capacity \_\_\_\_\_ 7.0 qt (6.6 L)  
Coolant Capacity \_\_\_\_\_ 14.0 qt (13.33 L)  
Emissions Controls \_\_\_\_\_ 3-way catalytic converter and internal engine features<sup>4</sup>  
Estimated EPA Fuel Economy (MPG City/Hwy):  
Two-Wheel Drive \_\_\_\_\_ 13/19  
Four-Wheel Drive \_\_\_\_\_ 13/18

<sup>4</sup> Meets Tier 1 requirements in all 50 states.

## TRANSMISSION: GETRAG 238 – MANUAL, 6-SPEED OVERDRIVE

Availability \_\_\_\_\_ Standard – all with 3.7L engines

Description \_\_\_\_\_ Synchronized in all gears

### Gear Ratios:

1st	_____	4.23
2nd	_____	2.53
3rd	_____	1.67
4th	_____	1.23
5th	_____	1.00
6th	_____	0.79
Reverse	_____	3.84
Overall Top Gear with 3.21 axle	_____	2.53
Overall Top Gear with 3.55 axle	_____	2.80
Overall Top Gear with 3.92 axle	_____	3.10

## TRANSMISSION: 545RFE – AUTOMATIC, 5-SPEED OVERDRIVE

Availability \_\_\_\_\_ Standard with 4.7L/5.7L engines

Description \_\_\_\_\_ Three planetary gear sets, one overrunning clutch,  
full electronic control, electronically-controlled converter clutch

### Gear Ratios:

1st	_____	3.00
2nd	_____	1.67 – upshift; 1.50 kick-down
3rd	_____	1.00
4th	_____	0.75
5th	_____	0.67
Reverse	_____	3.00
Overall Top Gear with 3.21 axle	_____	2.15
Overall Top Gear with 3.55 axle	_____	2.38
Overall Top Gear with 3.92 axle	_____	2.63
Overall Top Gear with 4.10 axle	_____	2.75

## TRANSMISSION: 42RLE – AUTOMATIC, 4-SPEED OVERDRIVE

Availability \_\_\_\_\_ Optional – all with 3.7L engines

Description \_\_\_\_\_ Hydraulic control, electronically-controlled governor,  
overdrive lockout and converter clutch

### Gear Ratios:

1st	_____	2.84
2nd	_____	1.57
3rd	_____	1.00
4th	_____	0.69
Reverse	_____	2.21
Overall Top Gear with 3.55 axle	_____	2.45
Overall Top Gear with 3.92 axle	_____	2.70

### TRANSFER CASE: NVG243

Availability \_\_\_\_\_ Standard  
Type \_\_\_\_\_ Part Time  
Shift Mechanism \_\_\_\_\_ Electronic  
Available Speeds \_\_\_\_\_ 2 Speed  
Low Range Ratio \_\_\_\_\_ 2.72  
Center Differential \_\_\_\_\_ None

Operating Modes:

- 2WD High
- 4WD High, Locked
- Neutral
- 4WD Low, Locked

### TRANSFER CASE: NVG246

Availability \_\_\_\_\_ Optional  
Type \_\_\_\_\_ On Demand  
Shift Mechanism \_\_\_\_\_ Electronic  
Available Speeds \_\_\_\_\_ 2 Speed  
Low Range Ratio \_\_\_\_\_ 2.72  
Center Differential \_\_\_\_\_ None

Operating Modes:

- 2WD High
- Auto 4WD
- 4WD High, Locked
- Neutral
- 4WD Low, Locked

## ELECTRICAL SYSTEM

Alternator \_\_\_\_\_ 160 Amp

Battery (Standard) \_\_\_\_\_ Group 65, low maintenance, 600 CCA

Battery (Optional, Part of Trailer Tow Group) \_\_\_\_\_ Group 65, low maintenance, 750 CCA

## BRAKES

Front:

Size \_\_\_\_\_ 13.2 in x 1.1 in (336 mm x 28 mm)

Type \_\_\_\_\_ Vented disc with 2.13 in (54 mm) two-piston pin-slider caliper

Swept Area \_\_\_\_\_ 292 sq in (1884 sq cm)

Rear:

Size \_\_\_\_\_ 13.8 in x 0.87 in (352 mm x 22 mm)

Type \_\_\_\_\_ Solid disc with 2.13 in (54 mm) single-piston pin-slider caliper

Swept Area \_\_\_\_\_ 274 sq in (1768 sq cm)

Power Assist Type \_\_\_\_\_ Dual-rate, tandem diaphragm vacuum

## DIMENSIONS AND CAPACITIES

### REGULAR CAB PICKUP

<i>Model – Tire Size</i>	<i>2WD – 245/70R17</i>		<i>4WD – 245/70R17</i>	
<b>Box Length</b>	<i>Short</i>	<i>Long</i>	<i>Short</i>	<i>Long</i>
Wheelbase (nominal) – in (mm)	120 (3048)	140 (3556)	120 (3048)	140 (3556)
Track, Front – in (mm)	68 (1728.2)	68 (1728.2)	68.1 (1730)	68.1 (1730)
Track, Rear – in (mm)	67.5 (1714.5)	67.5 (1714.5)	67.5 (1714.5)	67.5 (1714.5)
Overall Length – in (mm)	209 (5308.6)	226.9 (5764.5)	209 (5308.6)	226.9 (5764.5)
Overall Width – in (mm)	79.4 (2016.6)	79.4 (2016.6)	79.4 (2016.6)	79.4 (2016.6)
Overall Height – in (mm)	73.4 (1864.3)	73.3 (1861.8)	74.3 (1887.2)	74.1 (1882.2)
<b>Ground Clearance</b>				
- Front Axle – in (mm)	8.7 (219.8)	8.6 (219.4)	8.1 (204.6)	8.1 (204.6)
- Rear Axle – in (mm)	7.7 (194.8)	7.7 (194.8)	7.7 (194.8)	7.7 (194.8)
Open Tailgate to Ground – in (mm)	32.2 (817.8)	32.2 (817.8)	33 (838.2)	32.9 (835.6)
Pickup Body Height – in (mm)	52.3 (1328)	52.4 (1330)	53.1 (1348)	53.1 (1348)
Approach Angle, degrees	17.3°	17.2°	19.3°	19.2°
Departure Angle, degrees	23.6°	23.4°	24.4°	24.3°
Ramp Breakover Angle, degrees	21°	19.3°	17.1°	15.2°
Fuel Tank Capacity	26 gal (98 L) (Standard)	32 gal (121 L) (Standard)	26 gal (98 L) (Standard)	32 gal (121 L) (Standard)

## QUAD CAB® PICKUP

<b>Model – Tire Size</b>	<b>2WD – 245/70R17</b>	<b>4WD – 245/70R17</b>
Wheelbase (nominal) – in (mm)	140 (3556)	140 (3556)
Track, Front – in (mm)	68 (1728.2)	68.1 (1730)
Track, Rear – in (mm)	67.5 (1714.5)	67.5 (1714.5)
Overall Length – in (mm)	229 (5816.6)	229 (5816.6)
Overall Width – in (mm)	79.4 (2016.6)	79.4 (2016.6)
Overall Height – in (mm)	73.9 (1877.4)	74.8 (1899.4)
<b>Ground Clearance</b>		
- Front Axle – in (mm)	8.6 (219.4)	8.1 (204.6)
- Rear Axle – in (mm)	7.7 (194.7)	7.7 (194.7)
Open Tailgate to Ground – in (mm)	32.1 (816.1)	32.9 (836)
Pickup Body Height – in (mm)	52.2 (1325)	53.0 (1346)
Approach Angle, degrees	17.2°	19.2°
Departure Angle, degrees	23.4°	24.3°
Ramp Breakover Angle, degrees	19.3°	15.2°
Fuel Tank Capacity	26 gal (98 L) (Standard) 32 gal (121 L) (Optional)	26 gal (98 L) (Standard) 32 gal (121 L) (Optional)

## CREW CAB PICKUP

<b>Model – Tire Size</b>	<b>2WD – 245/70R17</b>	<b>4WD – 245/70R17</b>
Wheelbase (nominal) – in (mm)	140 (3556)	140 (3556)
Track, Front – in (mm)	68 (1728.2)	68.1 (1730)
Track, Rear – in (mm)	67.5 (1714.5)	67.5 (1714.5)
Overall Length – in (mm)	227.5 (5779.3)	227.5 (5779.3)
Overall Width – in (mm)	79.4 (2016.6)	79.4 (2016.6)
Overall Height – in (mm)	73.9 (1878.2)	74.8 (1900.1)
<b>Ground Clearance</b>		
- Front Axle – in (mm)	8.6 (219.4)	8.1 (204.6)
- Rear Axle – in (mm)	7.7 (194.7)	7.7 (194.7)
Open Tailgate to Ground – in (mm)	32.1 (816.1)	32.9 (835.6)
Pickup Body Height – in (mm)	52.1 (1323)	52.9 (1343)
Approach Angle, degrees	17.2°	19.2°
Departure Angle, degrees	20.9°	21.9°
Ramp Breakover Angle, degrees	19.3°	15.2°
Fuel Tank Capacity	26 gal (98 L) (Standard) 32 gal (121 L) (Optional)	26 gal (98 L) (Standard) 32 gal (121 L) (Optional)

**CARGO BOX**

<b><i>Nominal Box Size</i></b>	<b><i>5 ft 7 in (Crew)</i></b>	<b><i>6 ft 4 in (Regular or Quad<sup>®</sup>)</i></b>	<b><i>8 ft (Regular)</i></b>
SAE Volume, cu ft (cu m)	45.9 (1.3)	52.4 (1.48)	74.9 (2.12)
Length at Floor, Tailgate Closed – in (mm)	67.4 (1712.4)	76.3 (1938.5)	96.3 (2446.5)
Cargo Width – in (mm)	66.4 (1686.9)	66.4 (1686.9)	66.4 (1686.9)
Distance Between Wheelhouses – in (mm)	51 (1295.4)	51 (1295.4)	51 (1295.4)
Depth – in (mm)	20.0 (508)	20.1 (510.5)	20.2 (513.2)
Tailgate Opening Width in – (mm)	60.6 (1538)	60.6 (1538)	60.6 (1538)

## ACCOMMODATIONS

<b>Model</b>	<b>Regular Cab</b>	<b>Quad Cab®</b>	<b>Crew Cab</b>
Seating Capacity, F/R	3/0	3/3	3/3
<b>Front</b>			
- Head Room – in (mm)	40.8 (1037.5)	41.3 (1049.7)	41 (1040.5)
- Leg Room – in (mm)	41 (1041.3)	41 (1041.3)	41 (1041.3)
- Shoulder Room – in (mm)	66 (1676.4)	66 (1676.5)	66 (1676.5)
- Hip Room – in (mm)	63.6 (1615.4)	63.2 (1604.6)	63.6 (1615.4)
- Seat Travel – in (mm)	9.0 (230.0)	9.0 (230.0)	9.0 (230.0)
- Recliner Range (deg)	42°	42°	42°
<b>Rear</b>			
- Head Room – in (mm)	N/A	39.7 (1007.3)	39.9 (1013.5)
- Leg Room – in (mm)	N/A	36.8 (934.9)	39.4 (999.8)
- Shoulder Room – in (mm)	N/A	65.7 (1670)	65.7 (1670)
- Hip Room – in (mm)	N/A	62.9 (1598.3)	63.2 (1605.2)
<b>Interior Volume</b>			
- Front – cu ft (cu m)	64 (1.81)	60.8 (1.72)	61 (1.73)
- Rear – cu ft (cu m)	N/A	54.9 (1.56)	59.9 (1.7)

## BODY/CHASSIS

<i>Model</i>	<i>2WD</i>	<i>4WD</i>
Layout	Longitudinal, front engine	Longitudinal, front engine, transfer case
Construction	Ladder-type frame, steel cab, double-wall steel pickup box	Ladder-type frame, steel cab, double-wall steel pickup box

## SUSPENSION

<i>Model</i>	<i>2WD</i>	<i>4WD</i>
Front	Upper and lower "A" arms, coil springs, twin tube shock absorbers, stabilizer bar	Upper and aluminum lower "A" arms, coil over twin tube shock absorbers, stabilizer bar
Rear	5-link with track bar, coil springs, stabilizer bar, twin tube shock absorbers, solid axle	5-link with track bar, coil springs, stabilizer bar, twin tube shock absorbers, solid axle

## STEERING

### REGULAR CAB PICKUP

<i>Model</i>	<i>2WD</i>		<i>4WD</i>	
	Short Box	Long Box	Short Box	Long Box
Box Length				
Wheel Base (nominal) - in (mm)	120 (3048)	140 (3556)	120 (3048)	140 (3556)
Overall Steering Ratio	19.1:1	17.89:1	19.1:1	17.89:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter - 17" Tire in (mm)	39.481 (12.08)	45.109 (13.74)	39.539 (12.05)	45.319 (13.81)
Turning Diameter - 20" Tire in (mm)	39.279 (11.97)	46.23 (14.09)	39.539 (12.05)	45.361 (13.82)
Turning Diameter - TRX4 in (m)	N/A	N/A	39.185 (11.94)	44.916 (13.69)

### QUAD CAB<sup>®</sup> PICKUP

<i>Model</i>	<i>2WD</i>	<i>4WD</i>
Wheel Base (nominal) - in (mm)	140 (3556)	140 (3556)
Overall Ratio	17.89:1	17.89:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter - 17" Tire - in (m)	45.109 (13.74)	45.319 (13.81)
Turning Diameter - 20" Tire - in (m)	46.23 (14.09)	45.361 (13.82)
Turning Diameter - TRX4 - in (m)	N/A	44.916 (13.69)

## CREW CAB PICKUP

<i>Model</i>	<i>2WD</i>	<i>4WD</i>
Wheel Base (nominal) - in (mm)	140 (3556)	140 (3556)
Overall Ratio	17.89:1	17.89:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter - 17" Tire - in (m)	45.109 (13.74)	45.319 (13.81)
Turning Diameter - 20" Tire - in (m)	46.23 (14.09)	45.361 (13.82)
Turning Diameter - TRX4 - in (m)	N/A	44.916" (13.69)

## MAXIMUM PAYLOAD CAPACITIES\*

<i>Regular Cab Short Box</i>	<i>Engine</i>	<i>Transmission</i>	<i>4WD / 2WD</i>	<i>GVW (lbs)</i>	<i>Payload (lbs)</i>
	3.7L	Manual	4X2	6025	1480
	3.7L	Automatic	4X2	6025	1490
	4.7L	Automatic	4X2	6025	1290
	4.7L	Automatic	4X4	6350	1380
	5.7L	Automatic	4X2	6200	1470
	5.7L	Automatic	4X4	6350	1390
<i>Regular Cab Long Box</i>	<i>Engine</i>	<i>Transmission</i>	<i>4WD / 2WD</i>	<i>GVW (lbs)</i>	<i>Payload (lbs)</i>
	3.7L	Manual	4X2	6600	1840
	3.7L	Automatic	4X2	6600	1850
	4.7L	Automatic	4X2	6600	1750
	4.7L	Automatic	4X4	6600	1470
	5.7L	Automatic	4X2	6600	1690
	5.7L	Automatic	4X4	6600	1440
<i>Quad Cab® Short Box</i>	<i>Engine</i>	<i>Transmission</i>	<i>4WD / 2WD</i>	<i>GVW (lbs)</i>	<i>Payload (lbs)</i>
	3.7L	Manual	4X2	6700	1780
	3.7L	Automatic	4X2	6700	1790
	4.7L	Automatic	4X2	6700	1710
	4.7L	Automatic	4X4	6700	1430
	5.7L	Automatic	4X2	6700	1630
	5.7L	Automatic	4X4	6700	1390
<i>Crew Cab Short Box</i>	<i>Engine</i>	<i>Transmission</i>	<i>4WD / 2WD</i>	<i>GVW (lbs)</i>	<i>Payload (lbs)</i>
	4.7L	Automatic	4X2	6800	1650
	4.7L	Automatic	4X4	6800	1410
	5.7L	Automatic	4X2	6800	1640
	5.7L	Automatic	4X4	6800	1360

\* Maximum values shown, payload will vary depending on vehicle trim level and option content.

## ESTIMATED TRAILER TOW CAPACITIES\*

**3.7L Regular Cab – Short Box (1L61) - ST**

**3.7L Regular Cab – Long Box (1L62) - ST**

**3.7L Quad Cab® – Short Box (1L41) - ST**

<b>Engine</b>	<b>4WD 2WD</b>	<b>Trans</b>	<b>Axle</b>	<b>Tire</b>	<b>Trim</b>	<b>GCW (lbs)</b>	<b>Quad Cab® Short Box Max Trailer (lbs)</b>	<b>Reg Cab Short Box Max Trailer (lbs)</b>	<b>Reg Cab Long Box Max Trailer (lbs)</b>
3.7L	4X2	Auto (4-Spd)	3.92	17" P245	ST	8,500	3,450	3,800	N/A
			3.92	17" P265	ST	8,500	N/A	N/A	3,600
			3.55	17" P245	ST	8,500	N/A	3,800	N/A
		Man (6-Spd)	3.92	17" P245	ST	8,000	2,950	3,300	N/A
			3.92	17" P265	ST	8,000	N/A	N/A	3,100
			3.21	17" P245	ST	8,000	N/A	3,300	N/A

\*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

**4.7L Regular Cab – Short Box (1L61, 1H61, 6L61, 6H61) – ST, SLT, TRX**

**4.7L Regular Cab – Long Box (1L62, 1H62, 6L62, 6H62) – ST, SLT, TRX**

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW (lbs)	Reg Cab Short Box Max Trailer (lbs)	Reg Cab Long Box Max Trailer (lbs)
4.7L	4X2	Auto (5-Spd)	3.92	17" P265	ST, SLT, TRX	12,500	7,600	7,450
			3.92	20" P275	SLT	11,500	6,500	6,350
			3.55	17" P245 or P265	ST, SLT, TRX	11,500	6,600	6,450
			3.55	20" P275	SLT	10,500	5,500	5,350
			3.21	17" P245	ST, SLT	10,500	5,600	5,450
	4X4	Auto (5-Spd)	3.92	17" P265	ST, SLT	12,500	7,400	7,200
			3.92	20" P275 or 17" LT275	SLT, TRX-off road	11,500	6,300	6,100
			3.55	17" P245 or P265	ST, SLT	11,500	6,400	6,200
3.55			20" P275	SLT	10,500	5,300	5,100	

\*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

**4.7L Quad Cab® – Short Box (1L41, 1H41, 6L41, 6H41) – ST, SLT, TRX**

**4.7L Crew Cab – Short Box (1L90, 1H90, 6L90, 6H90) – ST, SLT, TRX**

Engine	4WD 2WD	Trans	Axle	Tire	Trim	GCW (lbs)	Reg Cab Short Box Max Trailer (lbs)	Reg Cab Long Box Max Trailer (lbs)
4.7L	4X2	Auto (5-Spd)	3.92	17" P265	ST, SLT, TRX	12,500	7,200	7,350
			3.92	20" P275	SLT	11,500	6,100	6,200
			3.55	17" P245 or P265	ST, SLT, TRX	11,500	6,200	6,350
			3.55	20" P275	SLT	10,500	5,100	5,200
			3.21	17" P245	ST, SLT	10,500	5,200	5,350
	4X4	Auto (5-Spd)	3.92	17" P265	ST, SLT	12,500	6,950	7,100
			3.92	20" P275 or 17" LT275	SLT, TRX-off road	11,500	5,950	5,950
			3.55	17" P245 or P265	ST, SLT	11,500	5,950	6,100
3.55			20" P275	SLT	10,500	5,750	5,850	

\*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

**5.7L Regular Cab – Short Box (1L61, 1H61, 6L61, 6H61) – ST, SLT, TRX, Sport, R/T**  
**5.7L Regular Cab – Long Box (1L62, 1H62, 6L62, 6H62) – ST, SLT, TRX**

<b>Engine</b>	<b>4WD 2WD</b>	<b>Trans</b>	<b>Axle</b>	<b>Tire</b>	<b>Trim</b>	<b>GCW (lbs)</b>	<b>Reg Cab Short Box Max Trailer (lbs)</b>	<b>Reg Cab Long Box Max Trailer (lbs)</b>
5.7L	4X2	Auto (5-Spd)	4.10	20" P275	Sport, R/T	11,000	5,000	N/A
			3.92	17" P265	ST, SLT, TRX	14,000	9,100	8,950
			3.92	20" P275	SLT	13,000	8,000	7,850
			3.55	17" P245 or P265	ST, SLT, TRX	13,000	8,100	7,950
			3.55	20" P275	SLT	12,000	7,000	6,850
			3.21	17" P245	ST, SLT	11,000	6,000	5,900
	4X4	Auto (5-Spd)	3.92	17" P265	ST, SLT, Laramie	14,000	8,900	8,700
			3.92	20" P275 or 17" LT275	SLT, TRX-off road, Sport	13,000	7,800	7,600
			3.55	17" P245 or P265	ST, SLT	13,000	7,900	7,700
			3.55	20" P275	SLT, Sport	12,000	6,800	6,600

\*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).

**5.7L Quad Cab® – Short Box (1L41, 1H41, 1P41, 6L41, 6H41, 6P41) – ST, SLT, TRX, Sport, Big Horn, Lone Star, Laramie**

**5.7L Crew Cab – Short Box (1L90, 1H90, 1P90, 6L90, 6H90, 6P90) – ST, SLT, TRX, Sport, Big Horn, Lone Star, Laramie**

<b>Engine</b>	<b>4WD 2WD</b>	<b>Trans</b>	<b>Axle</b>	<b>Tire</b>	<b>Trim</b>	<b>GCW (lbs)</b>	<b>Crew Cab Short Box Max Trailer (lbs)</b>	<b>Quad Cab® Short Box Max Trailer (lbs)</b>
5.7L	4X2	Auto (5-Spd)	3.92	17" P265	ST, SLT, TRX, Laramie	14,000	8,700	8,800
			3.92	20" P275	SLT, Sport, Big Horn, Lone Star, Laramie	13,000	7,600	7,650
			3.55	17" P245 or P265	ST, SLT, TRX, Laramie	13,000	7,700	7,800
			3.55	20" P275	SLT, Sport, Big Horn, Lone Star, Laramie	12,000	6,600	6,650
			3.21	17" P245	ST, SLT	11,000	6,700	6,800
	4X4	Auto (5-Spd)	3.92	17" P265	ST, SLT, Laramie	14,000	8,400	8,550
			3.92	20" P275 or 17" LT275	SLT, TRX-off road, Sport, Big Horn, Lone Star, Laramie	13,000	7,300	7,400
			3.55	17" P245 or P265	ST, SLT, Laramie	13,000	7,400	7,550
			3.55	20" P275	SLT, Sport, Laramie	12,000	6,300	6,400

\*Maximum towing capacities shown with properly equipped vehicle and a 150-lb driver. Options, equipment, cargo and passengers must be deducted (see Dodge Trailer Tow Guide for specific details).